Frederic	k County Contract Number:
MPWA:	Number:
Date:	
To:	Division of Utilities & Solid Waste Management (DUSWM)
	ATTN: Chuck Seiser
	Department of Engineering and Planning
	4520 Metropolitan Court
	Frederick, Maryland 21704
From:	Contractor Name
	Address
	City, State Zip
	- · · · · · · · · · · · · · · · · · · ·
Re:	Project Name:
	· 3 · · · · · · · · · · · · · · · · · · ·
"Certific	eation Statement: By this submittal, I hereby represent that I have determined and
	all field measurements, field construction criteria, materials, dimensions, catalog
	and similar data and I have checked and coordinated each item with other applicable
	<u> </u>
approved	d shop drawings and all Contract requirements."
	Contractor Signature Date
NT 4 1	
Note 1:	Please denote (highlight, check numbers, or otherwise identify) the materials from the
	following list that you intend to use on this project.
	TO THE STATE OF TH
Note 2:	If you desire to use materials that DO NOT appear in the following list, provide
	substitution information in accordance with Section 1200 of the General Conditions and
	Standard Specifications for Water Mains, Sanitary Sewers and Related Structures.
	Failure to provide complete information will result in delays in the approval process and
	may affect the project schedule.

Note 3: This list and all substitution information shall be submitted to the Division of Utilities & Solid Waste Management (DUSWM) with the Proposal Package.

Frederick County Contract Number:			
MPWA Number:			
CAI	MTADV CEWI	7 D	
SAI	NITARY SEWI	2K	
Specification Section: 2570	PVC Pipe		
Standard Details: 1.1, 2.1, 4.1, 201.1, 201.2, 20	01.3.201.4.201.5.201	7 201 8 202 03 203 1 2	06.1. 206.2. 206.4
208.1, 209.1, 209.2, 210.1, 211.1, 213.2,213.3,		.7, 201.0, 202.03,203.1, 2	00.1, 200.2, 200.4,
Standard: SDR35, ASTM D3034 or ASTM F6	79: SDR26_ASTM D3	3034 or ASTM D2241	
Approved Manufacturer/Product	Type	Standard	Size
☐ Diamond Plastics Corp	1 JPC	Starati	Size
☐ Extrusion Technologies, Inc.			
☐ J-M Manufacturing Co., Inc			
□ National Pipe Co.			
☐ Plastic Trends, Inc.			
n	VOC LA LEW		
	VC Gasketed Fittings		
Specification Section: 2570	10.1.010.0		
Standard Details: 115.1, 201.3, 201.4, 210.1, 2		1004 ACT / D0044	
Standard: SDR35, ASTM D3034 or ASTM F6			G.
Approved Manufacturer/Product	Part#	Catalog #	Size
☐ GPK Products, Inc.			
☐ The Harrington Corp.			
☐ J-M Manufacturing Co., Inc.			
□ Multi Fittings Corp.			
□ Plastic Trends, Inc.			
Pre	cast Concrete Manhol	les	
Specification Section: 3360			
Standard Details: 201.1, 201.2, 201.3, 201.4, 2	01.5, 201.6, 201.7, 201	1.8, 202.2, 202.4	
Standard: ASTM C478, Type II Cement			
Approved Manufacturer/Product	Detail	Size	Other
□ Americast			
☐ Atlantic Concrete Products, Inc.			
☐ Advanced Drainage Structures			
☐ C. R. Semler, Inc.			
□ Terre-Hill			
	Samanata Cuada Dinas		
	Concrete Grade Rings		
Specification Section: 3360			
Standard Details: 5.3	maga May (2) Miss O	? The ten and a since -1.	ıld ha 2"
	Standard: ASTM C478, Type II Cement. Thickness: Max. 6"; Min. 2". The top grade ring should be 2".		
Approved Manufacturer/Product		Thickness	
□ Americast			

Page 2 of 14

Atlantic Concrete Products, Inc.Advance Drainage Structures

Prism Precast Products, LLC

□ C. R. Semler, Inc.

Fre	derick County Contract Number:		
MP	WA Number:		
	Pre	cast Cleanout Blocks	
Spe	cification Section: 2570		
Star	ndard Details: None, associated details 206.1	, 206.2, 206.4, 208.1, 209.1, 209.2	
Star	ndard: ASTM C478, Type II Cement.		
	Approved Manufacturer/Product	Sizes to be used	Configurations
	Prism Precast Products, LLC		
	Mayer Brothers, Inc.		
	Atlantic Precast Products, Inc.		
	Manhole Frame and	Cover: Lamp Hole Frame and C	Cover

Spe	ecification Section: 2570				
Sta	andard Details: 5.1, 5.2, 208.1				
Sta	Standard: ASTM A48 Grade 30				
			Use		
	Approved Manufacturer/Product	Frederick Co.	Sewer	Water	Private
	East Jordan Iron Works, Inc.				
	Capitol Foundry of Virginia, Inc.				
	Chesapeake Foundries, Inc.				

Manhole Adapters			
Specification Section: 2570			
Standard Details: 210.1, 212.1, 213.2			
Standard:			
Approved Manufacturer/Product Supplemental Information			
☐ Kor-N-Seal® NPC, Inc.			
□ A-LOK Products, Inc.			
☐ Press-Boot® Press-Seal Gasket Corp.			

Sewer Service Saddles

Specification Section: 2570

Standard Details: 205.1, 206.2

Standard: Only if shown on the plans or approved by the DUSWM

Approved Manufacturer/Product

Size Type of Pipe Part/Catalog # Catalog Cut Incl.

Sealtite® The General Engineering Co.

Romac Industries, Inc., "CB"

Sewer Service Saddles

Standard: Only if shown on the plans or approved by the DUSWM

Approved Manufacturer/Product

Size Type of Pipe Part/Catalog # Catalog Cut Incl.

Non-Shrink Grout			
Specification Section: 2570, 4200			
Standard Details: 201.1, 201.2, 202.3, 207.1, 21	Standard Details: 201.1, 201.2, 202.3, 207.1, 210.1		
Standard: Type II Cement, Corp of Engineers C	RD-588		
Approved Manufacturer/Product Supplemental Information			
☐ Thorite® Thoro System Products			
☐ Cem Patch			

Butyl Rubber Sealan	
Specification Section: 2570	

Frederick County Contract Number:		
MPWA Number:		
Standard Details: 5.3, 112.1		
Standard: AASHTO M-198, ³ / ₄ " diameter		
Approved Manufacturer/Product	Supplemen	tal Information
☐ Kent Seal®		
☐ Bidco Sealants, Inc.		
☐ ConSeal Concrete Sealants, Inc.	CS-102 (only)	
	halt Base Waterproofing	
Specification Section: 2570		
Standard Details: 112.1	_	
Standard: MIL-C-82052; MIL –P-23236P Cla		
Approved Manufacturer/Product	Define manuf	acturer to be used
□ Clipper Ship®		
	le Iron Pipe – Force Main	
Specification Section: 2570, 2550		
Standard Details:		
Standard: AWWA C151, C111, C104		
Approved Manufacturer/Product	Size	Class
☐ American Cast Iron Pipe		
☐ Atlantic States Cast Iron Pipe Co.		
☐ Griffin Pipe Products Co.		
☐ U.S. Pipe and Foundry Co.		
	mp Around Operations	
Specification Section:	1	
Standard Details: Shown on plans	□ Yes	□ No
Standard: As shown on approved plans	1 30 t D D t	N. I. ep
Approved Vendors	Minimum Pump Rate	Number of Pumps
□ Sun Belt Rentals		
Capital Rentals		
☐ Godwin Pumps		□ Yes
	LVD	
	ck-N-Bore Operations	
Specification Section: 2950		
Standard Detail: 211.1		
Standard: Casing – AWWA C-200; PVC pi		
Approved Vendors	Casing Spacers	End Seals
☐ Advance Products and Systems		☐ Models AWN &/or CAN
☐ Cascade Waterworks Manufacturing		□ Model CCES
Corrosion Control Products		□ Models S, C, or W

Frederick County Contract Number: MPWA Number:				
Ado	ditional Sewer			
Manufacturer & Product		Specifi	ication & Detail	
	WATER			
	Ductile Iron Pi	pe		
Specification Section: 2550				
Standard Details: 2.3, 101.1, 102.1, 103.1, 104.1				
Standard: AWWA C151, C111, C104; 3"-6" Cla				
Approved Manufacturer/Product	Spec	Si	ize	Class
☐ American Cast Iron Pipe				
Atlantic States Cast Iron Pipe Co.				
☐ Griffin Pipe Products Co.				
☐ U.S. Pipe and Foundry Co.				
Ductile Iron Fittings				
Specification Section: 2550		-		
Standard Details: 102.1, 103.1, 104.1, 105.1, 10	7.1			
Standard: AWWA C153, C111, C104; Class 350		10, C151; Class 2:	50	
Approved Manufacturer/Product	Spec	Size	Class	Type
□ SIGMA Corporation.				
☐ Tyler/Union Foundry Co.				
☐ U.S. Pipe and Foundry Co.				
☐ Griffin Pipe Products Co.				
	Valves			
Specification Section: 2550				
Standard Details: 108.1, 108.2, 112.1, 115.1, 11				
Standard: 2" Resilient seat, open left, threaded, A				
16" and larger, Butterfly Valve, open left, with in	dicator MJ AW	WA C504. All exp	osed nuts/bolts n	nust be stainless
steel on all valves.				
Approved Manufacturer/Product		Define size	s to be used	
☐ Kennedy Valve				
☐ Mueller Company				
□ M & H Valve Co.				
D Duntt Value				
□ Pratt Valve□ Clow Valve Company				

Fire Hydrants
Specification Section: 2550
Standard Details: 108.1, 108.2

ederick County Contract Number: PWA Number:			
andard: 6" MJ inlet, 51/4" valve, 2-2 ½" and 1-4 ½ erating nut, painted safety yellow.	" nozzles with N.S. t	hreads, 1 ½" open lef	t pentagonal
Approved Manufacturer/Product	Standard	Dewatering	Bury depth
American Darling B-62-B			
Kennedy Valve, Model K81 (Only models			
allowed in Walkersville)			
Mueller Company, Model A-423 (Only models			
allowed in Walkersville)			
Clow Medallion			

Brass Pipe and Fittings			
Specification Section: 2550			
Standard Details: 115.1, 116.1			
Standard: AWWA C800-01, Regular Strength			
Approved Manufacturer/Product Supplemental Information			
□ Merit Brass Company			
☐ Trenton Pipe Nipple Co.			

Joint Restraint, Mechanical Joint								
Specification Section: 2550								
Standard Details: 109.1								
Standard: 3" – 16", 350 psi; 18" & larger, 250 psi								
Approved Manufacturer/Product								
☐ Ebaa Iron, Inc.	□ Megalug®	1 100						
☐ The Ford Meter Box Co.	□ Uni-Flange®	1400						
□ SIGMA Corporation	☐ One-Lok, SDL							

	Joint Restraint, Push Joint								
Sp	Specification Section: 2550								
Sta	Standard Details:								
Sta	andard: Must be used with the appropriate	e fitti	ings and pipe; Bells to be p	ainte	ed red				
Approved Manufacturer/Product Type Sizes Pressure rating									
	American Cast Iron Pipe Co.		Fast Grip Gasket		4"-12"		350 psi		
					14"		250 psi		
	Griffin Pipe Products Co.		Field Lok 350 Gasket		4"-12"		250 psi		
	The Gripper Gasket Co.		Gripper Gasket		3"-16"		350 psi		
	U.S. Pipe and Foundry Co.		Field Lok 350 Gasket		4"-12"		250 psi		
	Tyler Pipe/Union Foundry		Clow Super Lock		6"-36"		350 psi		

Valve Boxes
Specification Section: 2550
Standard Details: 108.1, 108.2, 112.1, 114.1, 116.1

	ederick County Contract Number: PWA Number:		
Sta	andard: Cast Iron Screw Type 5 1/4" shaft	ASTN	1 A48, Grade 30, Bituminous coating; slide or slip type is
	OT acceptable	10 11.	into, state to, statement country, since of sup type is
	Approved Manufacturer/Product		Number
	Bingham & Taylor		4905 & 4906
]			
	Capitol Foundry		VB-FRED
	Capitol Foundry East Jordon Iron Works		VB-FRED 8550 Series
	1 ,	+	
	East Jordon Iron Works		8550 Series

	Tapping Sleeve						
Sp	Specification Section: 2550						
Sta	andard Details: 117.1						
Sta	Standard: Working Pressure, 200 psi unless otherwise noted on plans or specifications.						
	Approved Manufacturer/Product Number Sizes						
	American Flow Control		Series 1004	14" – 36"			
			Series 2800	4" – 16"			
	Tyler Pipe			6" – 12"			
	Mueller Company		H-615	4" – 24"			
	M&H Valve			6" – 12"			

Copper Tubing					
Specification Section: 2550					
Standard Details: 110.1, 110.2, 110.3, 110.4, 111.1					
Standard: Seamless, Type K, Soft, ASTM B88.	No joints allowed between main and meter vault.				
Approved Manufacturer/Product	Define sizes to be used				
☐ Cambridge Lee Industries, Inc.					
☐ Mueller Copper Tube Co.					

	Corporation Stop					
Specification Section: 2550						
Standard Details: 113.1						
Standard: Ball Valve, 300 psi working pressurequired.	re Gripper Style. For service	ees larger than one inch use tapped tees is				
Approved Manufacturer/Product	Number	Defines sizes to be used				
☐ The Ford Meter Box Co.	□ FB600					
	□ FB1000-G					
	□ FB1700-7					
☐ AY McDonald Mfg. Company	□ 4701B					
	□ 4701BT					
	□ 3149B					
☐ Mueller Company	□ B-25000					
Angle Ball Valves						
Specification Section: 2550						
Standard Details: 110.1, 110.2, 110.3, 110.4,	115.1					
Standard: Ball Valve, 300 psi working pressu	re. Locking Wing					

Page 7 of 14

Frederick County Contract Number:

M	PWA Number:		
	Approved Manufacturer/Product	Number	Size
	The Ford Meter Box Co.,	BA91-323W	3/4"
		BA91-444W	1"
		BA94-323W-G	3/4"
		BA94-444W-G	1"
	AY McDonald Mfg. Company	4602BYT	³ / ₄ ' x ³ / ₄ " x 02
		4604BY	³ / ₄ " x ³ / ₄ " x 02
		4604BY	1" x 1" x 04
	Mueller Company	B-24273	5/8" x 3/4" x 3/4"
		B-24273	1"

□ B-24278□ B-24278

□ 5/8" x 3/4" x 3/4"

	Iron Meter Yoke						
Sp	ecification Section: 2550						
Sta	andard Details: 110.1, 110.2, 110.3, 110.4						
Sta	nndard:						
	Approved Manufacturer/Product		Number	Size			
	The Ford Meter Box Co.		Y502				
			Y504				
	AY McDonald Mfg. Company		14-2				
			14-4				
	Mueller Company		H-5020				
			H-5040				

Expansion Connection							
Specification Section: 2550							
Standard Details: 110.1, 110.2, 110.3, 110.4							
Standard:							
Approved Manufacturer/Product	Number	Size					
☐ The Ford Meter Box Co.	□ EC-23	□ ³ / ₄ "					
	□ EC-4						
☐ AY McDonald Mfg. Company	□ 14-2EHG	□ ³ / ₄ "					
	□ 14-4EHG	□ 1"					
☐ Mueller Company	□ H-14234	□ ³/₄", 1"					

	Cartridge Style Angle Dual Check Valve						
Sp	Specification Section: 2550						
Sta	Standard Details: 110.1, 110.2, 110.3, 110.4						
Sta	andard:						
	Approved Manufacturer/Product		Number		Size		
	The Ford Meter Box Co.		HHCA94-323-G				
			HHCA91-444				
	Mueller Company		H-14466-A-05				
	AY McDonald Mfg. Company		12W3YQ 33		3/4"		

Fre	ederick County Contract Number:				
	PWA Number:				
1411					
			12W4YQ 44		
			12W41Q44		
	Conne	ctor	Assembly With Plug		
Sne	ecification Section: 2550	CtOI	Assembly with Flug		
	andard Details: 110.1, 110.2, 110.3, 110.4				
	andard:				
	Approved Manufacturer/Product		Number		Size
	The Ford Meter Box Co.		C14-33-G		
			C14-44-G		
			C14-66-G		
			C14-77-G		
	AY McDonald Mfg. Company		4754T		
	Mueller Company,		H-15451		
		Rı	anch Pieces		
Sno	ecification Section: 2550		unen i icces		
	andard Details: 110.1				
	andard: 1" CTS x Two 3/4" MIP, 71/2" Spacin	g			
200	Approved Manufacturer/Product	<u> </u>	Number		Size
	The Ford Meter Box Co.		U48-43		Sille
	AY McDonald Mfg. Company		08UTM		
	Mueller Company		H-15363		
	Tandem	Sett	ers for Individual PR	·V	
	ecification Section: 2550				
Sta	andard Details: 110.2, 110.3				
Sta	nndard:				
	Approved Manufacturer/Product		Number		Size
	The Ford Meter Box Co.		A-95095		□ ³/₄"
			TYA-4-95095-059		□ 1"
	Mueller Company		215B5020-R6A00		
	AY McDonald Mfg. Company		14L2 WDQQ332 X	996	
		re R	educing Valve (PRV)		
	ecification Section: 2550				
	andard Details: 110.5				
Sta	nndard:				
	Approved Manufacturer/Product		Number		Size
	CLA-VAL, Automatic Control Valves		□ Model 990		" with two reducing bushings
				□ 1°	,
		ncr	ete Meter Vaults		
	ecification Section: 2550				
	andard Details: 110.3, 110.5				
Sta	andard: CL-1, ASTM C76 and ASTM C141				
	Approved Manufacturer/Product	<u> </u>		Sizes to	be used
	Advanced Drainage Structures	<u> </u>			
	Mayer Brothers	<u> </u>			
	Prism Precast Products				

Page 9 of 14

Frederick County Contract Number:				
N	Лete	r Vault Covers		
Specification Section: 2550				
Standard Details: 110.5				
Standard: All holes for electronic meter readers	mus	t be 2" actual dimension.		
Approved Manufacturer/Product		Nun	nber	
☐ The Ford Meter Box Co.		A53TP		10T
		A53TTPP		10TT, Pit Ring & Lid
		A53HHT, extra heavy duty		11T, heavy duty
		EXT-24, Extension Ring		FL-24 Flange, use with Pit
				Ring
☐ AY McDonald Mfg. Company		74M53TP [74M32ATP]		74MPR10TTPP
		74M53ATTPP		74MPR11TP
		74MX24, Extension Ring		74MPR11TTPP
		74MPR10TP		
1-1/2" &	z 2"	Custom Meter Setters		
Specification Section: 2550				
Standard Details: 111.1	Standard Details: 111.1			
Standard: Include ball valve & check valve on bypass line				
Approved Manufacturer/Product		Number		Size
☐ The Ford Meter Box Co.		VBHH76-15BHC-44-66-G		□ 1 ½"
		VBHH77-15BHC-44-77-G		□ 2"
Mueller Company		B-2423-2, 15" riser		□ 1 ½"

т	Large Meter Vaults	
Specification Section: 2550, 3360		
Standard Details: 112.1, 112.2		
Standard: ASTM C-478; ASTM C-150, type II	cement	
Approved Manufacturer/Product	Size	
□ C.R. Semler, Inc.		
☐ Advanced Drainage Structure		
□ Oldcastle Precast		
☐ Smith-Midland, Corp.		
☐ A. C. Miller Concrete Products		
☐ Americast		
Large Meter Vault Ladders		
Specification Section: 2550		
Standard Details: 112.2		
Standard: Vertical Aluminum ladder with support extension		
Approved Manufacturer/Product	Model	
☐ Halliday Aluminum Ladder	☐ Series L1B with Series L1E Safety Extension	

□ B-2423-2, 15" riser

□ 20B615WDQQ666

□ 20B715WDQQ776

□ 1-1/2"

□ 2"

☐ AY McDonald Mfg. Company

Frederick County Contract Number:				
MPWA Number:				
2" Air	Re	lease/Vacuum Valve		
Specification Section: 2550				
Standard Details: 115.1				
Standard: 16 inch T-handle required				
Approved Manufacturer/Product		Nun	nber	
□ CLA-VAL Automatic Control Valves		362-CAV332		
☐ Crispin-Multiplex Manufacturing Co.		UL20		
□ Valmatic Valves		VM-22		
	tion	/ 2" Bronze Angle Valve		
Specification Section: 2550				
Standard Details: 115.1				
Standard: Use 2" tapped tee, AWWA threads, 2"	' bal	l corporation and 2" globe valv	ve	
Approved Manufacturer/Product		Nun	nber	
☐ The Ford Meter Box Co.		FB1600-7		
☐ AY McDonald Mfg. Company		3148B		
□ Mueller Company		B-20045		
□ Nibco, Inc.		T-311-Y, Angle Valve		
	Se	rvice Saddle		
Specification Section: 2570				
Standard Details:				
Standard: All Bronze Service Saddles				
Approved Manufacturer/Product		Sei	ries	
☐ The Ford Meter Box Co.		101B		202B
☐ Romac Industries, Inc.				
☐ AY McDonald Mfg. Company		3815 (single strap)		3825 (double strap)
☐ Mueller Company		BR1B		BR2B
		ack-N-Bore		
Specification Section:		uck IV Bole		
Standard Details: 123.1, 211.1				
Standard Details: 125.1, 211.1 Standard: Casing – AWWA C-200; DIP pipe – AWWA C-104				
Approved Vendors		Casing Spacers		End Seals
☐ Advance Products and Systems		Model SSI		Models AW &/or AC
☐ Cascade Waterworks Manufacturing	_	Model CCS	_	1.1000151111 00/01110
□ Corrosion Control Products	<u> </u>	1.10401 CCS		Models S, C or W
		nal Water Items		models b, C of W
List Manufacturer	11110		spec	cifications and detail
		LINE AUDI WIN MIC	171/1	

Page 11 of Revised: May 2013

Frederick County Contract Number: MPWA Number:				
G	rinder	Pumps		
		ssure Pipe		
Specification Section: 2570		-		
Standard Details: 213.2, 214.1, 217.1,301.1, 30	02.1, 303.	1, 304.1, 305.	1, 306.1, 307.1	
Standard: Gasketed, SDR21, PVC 1120, ASTM	D2241			
Approved Manufacturer/Product		Гуре	Standard	Size
□ CertainTeed Corporation				
□ National Pipe				
P	VC Press	ure Fitting		
Specification Section: 2570				
Standard Details: 213.2, 214.1, 217.1, 302.1, 30	03.1, 304.	1, 305.1, 306.	1, 307.1,	
Standard: Gasketed, SDR21, ASTM D2241				
Approved Manufacturer/Product]	Part#	Catalog #	Size
☐ Flo Control, Inc.				
☐ The Harrington Corp.				
	PVC	Pipe		
Specification Section: 2570		•		
Standard Details:				
Standard: Threaded, Schedule 80, ASTM D2464	4			
Approved Manufacturer/Product		Гуре	Standard	Size
□ North American Pipe Corporation				
□ Diamond Plastics				
I	PVC Pur	ole Primer		
Specification Section: 2570				
Standard Details:				
Standard:				
Approved Manufacturer/Product			Series	
☐ United Elchem Industries, Inc.	□ Uni	-Weld 8700		
	PVC (Cement		
Specification Section: 2570				
Standard Details:				
Standard: Solvent Type				
Approved Manufacturer/Product			Series	
☐ United Elchem Industries, Inc.	□ Uni	-Weld 1500		
	Grinde	r Pump		
Specification Section:				
Standard Details:				
Standard: Control panel must be within sight of	the grind	er unit.		
Approved Manufacturer/Product			Model	
□ Environmental One Corp.		□ Model #	DH071	

Page 12 of 14

Frederick County Contract Number:	
MPWA Number:	
	Brass Fittings
Specification: 2570	5
Standard Details:	
Standard: Threaded	
Approved Manufacturer/Product	Supplemental Information
☐ Lee Brass Company	
☐ Merit Brass Company	
Specification: 2570	Swing Check Valve
Standard Details:	
Standard Details. Standard: PVC	
Approved Manufacturer/Product	Type/Series
☐ Flo Control, Inc.	☐ Compression Type, Series 1500
The control, like.	Solvent Weld Type, Series 1520
	JF-//
	Curb Box
Specification Section: 2570	
Standard Details:	
Standard: Screw Type	
Approved Manufacturer/Product	Supplemental Information
☐ Tyler Pipe (#142R)	
	Detector Tape
Specification Section: 2570	
Standard Details:	
Standard: 3 inch wide, Safety Green	
Approved Manufacturer/Product	Supplemental Information
☐ Tyler Pipe (#142R)	
	Direct Bury Cable
Specification:	Detail:
Specification: 2570	
Standard Details:	
Standard: Type UF, Cable with ground wire, 14.	/2
Approved Manufacturer/Product	Supplemental Information

Page 13 of 14 Revised: May 2013

Frederick County Contract Number:	
MPWA Number:	

Materials not on the Pre Approved list shall be submitted in accordance with the General Conditions and Standard Specifications for Water Mains Sanitary Sewers and Related Structures, Sect 1200 I. General A. Description: B. Technical Submittals 1. Shop Drawings a.

Original Submittal: One each reproducible or six (6) legible prints each of all shop drawings shall be submitted to the Engineer for approval in accordance with the shop drawing submission schedule, etc.